
INVENTOR(S): Satoko ITO et al.
TITLE: SPARK PLUG FOR USE IN
INTERNAL COMBUSTION ENGINE
DOCKET NO.: NG8775US


FIG. 1



INVENTOR(S): Satoko ITO et al.
TITLE: SPARK PLUG FOR USE IN
INTERNAL COMBUSTION ENGINE


DOCKET NO .: NG8775US

FIG. 2



INVENTOR(S): Satoko ITO et al.
TITLE: SPARK PLUG FOR USE IN
INTERNAL COMBUSTION ENGINE
DOCKET NO.: NG8775US

FIG. 3



NEW APPLICATION INVENTOR(S): Satoko ITO et al. TITLE: SPARK PLUG FOR USE IN INTERNAL COMBUSTION ENGINE

DOCKET NO.: NG8775US

FIG. 4A





FIG. 4B



NEW APPLICATION

INVENTOR(S): Satoko ITO et al. TITLE: SPARK PLUG FOR USE IN INTERNAL COMBUSTION ENGINE

DOCKET NO.: NG8775US

FIG. 5

Comprehensive	Evaluation	×	×	၁	၁	В	A	A	В	A	В	В	A	A	A	A	A
Channeling	(mm)	0.71 X	0.12 A	0.23 B	0.56 C	0.27 B	0.17 A	0.18 A	0.24 B	0.19 A	0.26 B	0.39 B	0.19 A	0.19 A	0.38 B	0.39 B	0.17 A
Erosion	(mm ₃)	0.14 A	0'93 X	0.46 C	0.19 A	0.31 B	0.24 B	0.26 B	0.39 B	0.21 B	0.37 B	0.26 B	0.22 B	0.29 B	0.18 A	0.17 A	0.38 B
Components (wt%)	Z	94.0	86.0	90.5	89.5	90.0	868	88.0	86.0	90.0	90.3	89.7	89.9	87.0	93.5	93.5	0'98
	Si	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
	Mn	2.0	2.0	0	0	0	0.2	2.0	4.0	2.0	0	0	0.15	3.0	2.0	2.0	2.0
	ΑI	0.5	0.5	0	1.0	0.5	0.5	0.5	0.5	0.5	0.2	8.0	0.5	0.5	0.5	0.5	0.5
	Fe	1.0	0'9	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	1.0	1.5	2.0
	Ċ	1.0	0'9	5.0	5.0	5.0	2.0	5.0	5.0	3.0	5.0	5.0	5.0	5.0	1.5	1.0	5.0
Sample		1	2	က	4	2	9	7	8	6	10	11	12	13	14	15	16

Evaluation of erosion A: less than Evaluation of channeling A: less than Comprehensive evaluation X: At least

A: less than 0.2 B: 0.2 to less than 0.4 C: 0.4 to less than 0.6 X: 0.6 or more A: less than 0.2 B: 0.2 to less than 0.4 C: 0.4 to less than 0.6 X: 0.6 or more

X: At least either erosion or channeling is evaluated as X. C: At least either erosion or channeling is evaluated as C.


B: Erosion and channeling are both evaluated as B.


A: At least either erosion or channeling is evaluated as A, and neither erosion nor channeling is evaluated as X or B.

NEW APPLICATION
INVENTOR(S): Satoko ITO et al.
TITLE: SPARK PLUG FOR USE IN
INTERNAL COMBUSTION ENGINE
DOCKET NO.: NG8775US

Evaluation		U	8	В
Sink	(mm)	0.10	0.07	0.07
	ï	89.99	89.99	89.99
	Si	1.5	1.5	1.5
/t%)	C	0.001	0.003	0.003
Components (wt%)	Mn	2.0	2.0	2.0
Comp	AI	0.5	0.5	0.5
	Fe	3.0	3.0	3.0
	ငံ	3.0	3.0	3.0
Sample		17	18	18

NEW APPLICATION
INVENTOR(S): Satoko ITO et al.
TITLE: SPARK PLUG FOR USE IN
INTERNAL COMBUSTION ENGINE





NEW APPLICATION
INVENTOR(S): Satoko ITO et al.
TITLE: SPARK PLUG FOR USE IN

INTERNAL COMBUSTION ENGINE DOCKET NO.: NG8775US

